



AMT-15

AMT-12

# AMT-12

# AMT-15

## Lightweight Professional Loudspeakers

### Description:

The AMT-12 and AMT-15 Loudspeakers are designed to provide high-output music and sound reinforcement in a lightweight, cost-efficient package. Robust, high-sensitivity woofers and a Ferrofluid-treated 1.77-inch compression driver are combined with highly-evolved crossover network technology. The AMT-12 and AMT-15 create an output more precise and accurate sounding than that of any other loudspeakers in this class.

### Driver Complement:

#### Low Frequency:

AMT-12: One Apogee 12" cone-type high-sensitivity, low-mass driver

AMT-15: One Apogee 15" cone-type high-sensitivity, low-mass driver

#### High Frequency:

One Apogee 1.77"-diameter aluminum-alloy compression driver diaphragm with a 1" exit, utilizing a specially-designed Ferrofluid for damping and cooling of the voice coil

#### **Input Connectors:**

Speakon™ type; pins +1/-1 for input, +2/-2 for bypass loop

#### **Handles:**

Integrated carry handle molded into side of enclosure

#### **Grille:**

Heavy-gauge perforated steel

#### **Mounting Options:**

- Pole mount, using 1-3/8" (35mm) socket
- Stacking, using integral feet
- Suspended, using M8 threaded inserts (1.25mm pitch) – two on top of enclosure and two on bottom of enclosure
- Arrayable, 0-degree "tight pack" to 30 degrees of splay, using available Adjustable Rigging Beam Kit

#### **Enclosure Type:**

Lightweight, multi-vented molded enclosure utilizing extensive rib matrix for minimizing panel resonances

#### **Cabinet Construction:**

Mineral-filled polypropylene

#### **Options/Accessories:**

Adjustable Rigging Beam Kit, 0–30 degrees (Part # 109-2140)

### Engineering Data:

#### **Format:**

Passive/Two-way

#### **Dispersion:**

60° H × 45° V

#### **Frequency Response (1m on axis):**

AMT-12: 60 Hz to 20 kHz ± 3 dB  
AMT-15: 50 Hz to 20 kHz ± 3 dB

#### **Sensitivity (1W @ 1m):**

AMT-12: 96 dB SPL  
AMT-15: 98 dB SPL

#### **Nominal Impedance:**

8 ohms

#### **Max. Power Handling:**

AMT-12: 200 W continuous  
AMT-15: 300 W continuous

#### **Max. Sound Pressure Level:**

AMT-12: 119 dB, Peak: 125 dB  
AMT-15: 123 dB, Peak: 129 dB

#### **Dimensions:**

AMT-12: 23" H × 16.25" W × 13" D  
AMT-15: 27" H × 19" W × 15" D

#### **Weight:**

AMT-12: 37 lb.  
AMT-15: 47 lb.